

HPX-PT™

PRE-TORQUED
HOLDER
ASSEMBLY

ENSURES
PRECISE
INSTALLATION



HPX-PT pre-torqued holders incorporate high strength steel socket head cap screws to ensure accurate loading and sealing of the HPX™ rupture disc. The HPX-PT holder allows the disc to be correctly fitted in the workshop using precise recommended torque levels, prior to installation of the complete assembly between the flanges in the process system relief stream.

COMMON INSTALLATIONS

- Process equipment having glass or TEFLON® lined flanges that cannot provide the compression required to seal the rupture disc in the holder
- Installations where the piping arrangement restricts access preventing correct torque loading of the flange fasteners
- Challenging processes requiring regular removal of the rupture disc and holder assembly for inspection
- Applications requiring leak testing of the rupture disc assembly prior to installation in the piping system

FEATURES

- Allows a precise torque load to be applied in the controlled environment of a workshop prior to installation
- Maintains precise loading of the rupture disc where poor flange alignment and gasket cold flow may be an issue
- Pre-torqued holder screws are protected with NEDOX® surface coating that will not chip, peel or flake off. The NEDOX® coating prevents wear, sticking and galling of the screws, and provides corrosion resistance superior to stainless steel, and chromium or nickel platings

SPECIFICATIONS

- Compatible with the HPX™ rupture disc products
- Standard sizes ranging from 1" through 8" (25 mm to 160 mm)
- Available in sizes and bolting classes shown in table on next page

STANDARD MATERIALS AVAILABLE

- | | |
|----------------|-----------------------|
| ➤ Carbon Steel | ➤ 316 Stainless Steel |
| ➤ MONEL® | ➤ HASTELLOY®C |

AVAILABLE OPTIONS

- | | |
|--|-------------------------------|
| ➤ Alternate heights | ➤ Gauge taps in holder outlet |
| ➤ Flange studs & nuts, alloy steel or 316 SS | ➤ J-Hook on holder inlet |
| ➤ Corrosion resistance enhancement by adding a TEFLON® coating or TANTALINE® treatment | |



HPX-PT PRE-TORQUED HOLDER ASSEMBLY



HPX-PT PRE-TORQUED HOLDER WITH SOCKET HEAD CAP SCREWS

HPX-PT HOLDER // Weights, Dimensions & Bolting Classes

SIZE	OUTSIDE DIAMETER	HEIGHT	WEIGHT	BOLTING CLASSES							
				ASME		DIN		JIS			
in mm	in mm	in mm	lb kg								
1" 25 mm	3.63 92,2	1.80 45,7	3.34 1,51	150	300/600	10/40		10/20	30/40		
1 1/2" 40 mm	4.63 117,6	2.04 51,8	6.39 2,90	150	300/600	10/40		10/20	30/40		
2" 50 mm	5.25 133,4	2.36 59,9	9.31 4,22	150	300/600	10/40		10	16/20	30/40	
3" 80 mm	7.00 177,8	3.21 81,5	22.21 10,07	150	300/600	10/40		10	16/20	30/40	
4" 100 mm	8.10 205,7	3.97 100,8	34.02 15,43	150	300	10/16	25/40	10	16/20	30/40	
6" 150 mm	10.44 265,2	5.64 143,3	57.54 26,10	150	300	10/16	25/40	10	16/20	30/40	
8" 200 mm	12.88 327,1	7.26 184,4	101.70 46,13	150	300	10	16	25	40	16/20	30/40

TEFLON® is a registered trademark of E.I. du Pont de Nemours and Company used under license // NEDOX® is a registered trademark of General Magnaplate
 TANTALINE® is a registered trademark of Tantalum Technologies A/S Corporation
 MONEL® is a registered trademark of the Inco family of companies // HASTELLOY® is a registered trademark of Haynes International

<p>Continental Disc Corporation</p>	<p>GROTH CORPORATION a Continental Disc company</p>	<p>HEADQUARTERS // 3160 W. Heartland Drive Liberty, MO 64068 USA Ph (816) 792 1500 Fax (816) 792 2277 sales@contdisc.com</p>	<p>contdisc.com</p>
-------------------------------------	---	---	---------------------

<p>THE NETHERLANDS Energieweg 20 2382 NJ Zoeterwoude-Rijndijk The Netherlands Ph +(31) 71 5412221 Fax +(31) 71 5414361 cdnl@contdisc.com</p>	<p>CHINA Room 910, Tower B, COFCO Plaza No. 8 JianGuoMenNei Avenue Beijing (100005), P.R. China Ph +(86) 10 522 4885 Fax +(86) 10 6522 2885 cdchina@contdisc.com</p>	<p>INDIA 423/P/11, Mahagujarat Industrial Estate, Moraiya, Sarkhej-Bavla Road, Ahmedabad (GJ) 382213 INDIA Ph +(91) 2717 619 333 Fax +(86) 10 6522 2885 gcempl@contdisc.com</p>
--	--	---